

• YOUR  
• SMART  
• ENERGY



# SMILE-G3-T4/T5/T6/T8/T10

RESIDENTIAL SERIES

## POWER

4 / 5 / 6 / 8 / 10 kW

## CAPACITY

3.8 ~ 46.0 kWh with  
3.8 kWh Battery Module

4.0 ~ 24.0 kWh with  
4.0 kWh Battery Module



reddot design award 2022

GOOD DESIGN AWARD



3 MPPT for Higher PV Input

Bypass Function for Series Battery

Safer with Aerosols Inside the Battery

Capable of 150% Unbalancing per Phase

Compatible with EV Charger and Heat Pump

# SMILE-G3-T4/T5/T6/T8/T10



Model	SMILE-G3-T4	SMILE-G3-T5	SMILE-G3-T6	SMILE-G3-T8	SMILE-G3-T10
<b>System Specifications</b>					
Nominal Output Power	4 kW	5 kW	6 kW	8 kW	10 kW
Capacity Range	3.8 ~ 46.0 / 4.0 ~ 24.0 kWh (95% DoD)				
Battery Chemistry	LFP (LiFePO4)				
Warranty	10 Years Product Warranty, 10 Years Battery Performance Warranty				
<b>Inverter Technical Specifications</b>					
Model	SMILE-G3-T4-INV	SMILE-G3-T5-INV	SMILE-G3-T6-INV	SMILE-G3-T8-INV	SMILE-G3-T10-INV
Coupling	Hybrid	Hybrid	Hybrid	Hybrid	Hybrid
Max. PV Input Power	8 kW	10 kW	12 kW	16 kW	20 kW
Max. PV Input Current	16 A / 16 A / 16 A				
Max. PV Input Voltage	1000 V				
MPPT Number / Max. Input Strings Number per MPPT	3 / 1				
MPPT Voltage Range	140 ~ 950 V				
Max. PV Short-Circuit Current	24 A / 24 A / 24 A				
Max. Charging/Discharging Current	40 A				
Max. Charging/Discharging Power	4 kW	5 kW	6 kW	8 kW	10 kW
Rated Frequency	50 / 60 Hz				
Rated Voltage	220 V / 380 V, 230 V / 400 V				
Phase	Three Phase				
Rated Output Power (Grid Port)	4 kW	5 kW	6 kW	8 kW	10 kW
Rated Output Current (Grid Port)	5.8 A	7.3 A	8.7 A	11.6 A	14.5 A
Rated Output Power (Backup Port)	4 kW	5 kW	6 kW	8 kW	10 kW
Rated Input Power (on-grid)	8 kW	10 kW	12 kW	16 kW	20 kW
Backup	UPS				
Communication	Ethernet / WiFi / Modbus / API				
Relative Humidity	0 ~ 90% (No Condensation)				
Dimensions (W x D x H)	610 x 212.5 x 416 mm				
Weight	26.7 kg				
IP Protection	IP65				
Safety	IEC 62109-1/-2				
EMC	IEC 61000-6-1/-3				
Overvoltage Category	DC II				
Noise	≤ 30 dB				
Grid Regulation	VDE 4105, EN 50549-1, VDE0126-01-01, NC RFG				
Maximum / European Efficiency	97.6 % / 96.8 %				

## Battery Technical Specifications

Module Model	SMILE-G3-BAT-3.8S	SMILE-G3-BAT-4.0S
Module Capacity	3.8 kWh	4.0 kWh
Usable Capacity	3.6 kWh	3.8 kWh
Depth of Discharge (DoD)	95 %*	95 %*
Nominal Voltage	96 V	96 V
Max. Charging/Discharging Current	40 A**	42 A
Operating Temperature Range	-10°C ~ 50 °C****	-10°C ~ 60 °C****
Cycle Life	10000****	10000****
Battery Modules Connection	1 ~ 12 in Series	1 ~ 6 in Series
IP Protection	IP21	IP65
Dimensions (W x D x H)	610 x 212.5 x 435 mm	610 x 212.5 x 435 mm
Weight	39.2 kg	42.5 kg
Noise	≤ 35 dB	≤ 25 dB
Fire-Fighting	Aerosol	N/A

\* Test condition: Max. 0.5C charge/discharge at 25±2°C.

\*\* 50A discharging current sustainable for 30 minutes in off-grid operation.

\*\*\* 40A discharging current sustainable for 30 minutes in off-grid operation.

\*\*\*\* Max. charge/discharge current derating may occur with changes in temperature and SoC.

\*\*\*\*\* Under specific test conditions.



Alpha ESS Co., Ltd.

+86 513 8060 6891  
 info@alpha-ess.com  
 www.alphaess.com  
 No. 1086, Bihua Road,  
 Nantong Hi-Tech Zone,  
 Jiangsu Province, China

Alpha ESS Italy S.r.l.  
 +39 339 462 4288  
 info@alphaess.it  
 www.alphaess.com  
 Via Del Molinuzzo 83,  
 59100 Prato (PO), Italy

Alpha ESS Europe GmbH

+49 610 3459 1601  
 europe@alpha-ess.de  
 www.alphaess.de  
 Horizon Tower 17.0G  
 Alfred-Herrhausen-Allee 3-5  
 65760 Eschborn, Germany

Alpha ESS UK Ltd.  
 +44 0330 043 2610  
 info@alpha-ess.com  
 Drake house, Long street,  
 Dursley, GL11 4HH UK

Alpha ESS Australia Pty. Ltd.

+61 02 9000 7676  
 techsupport@alphaess.au  
 www.alphaess.com  
 8/15-21 Gibbes Street,  
 Chatswood,  
 NSW 2067 Australia

Alpha ESS USA, Inc.  
 +1 408 368 7828  
 usa@alpha-ess.com  
 Unit 5 2180 S Ivanhoe St,  
 Denver, CO 80222 USA

Alpha ESS International Pte. Ltd.

+65 6513 1125 / +65 6513 1126  
 Singapore@alpha-ess.com  
 2 Corporation Road #01-06A  
 Corporation Place 618494  
 Singapore

Alpha ESS Korea Co., Ltd.  
 info@alpha-ess.com  
 2F, 19-4, Nohyeong 11-gil,  
 Jeju-si, Jeju-do, Republic  
 of Korea

Alpha ESS South Africa (Pty) Ltd.

measervice@alpha-ess.com  
 La Rocca Office Park, Block  
 B1 321 Main Road, Bryanston,  
 Johannesburg, 2191